

# Options

	1010	1015	1020	1025
 <b>ECO-EFFICIENCY</b>				
Low-energy drive	•	•	•	•
Efficient LED lighting	•	•	•	•
Automatic car lighting switch off	•	•	•	•
Landing illumination control	○	○	○	○
Lift stand-by mode	○	○	○	○
 <b>ADAPTABILITY</b>				
Flexible controller location	○	○		
Lift well enclosure	○	○	○	○
Reduced headroom (with safety space)	○	○	○	○
Reduced pit (with safety space)	○	○	○	○
Accessible space below the pit	○	○	○	○
 <b>CONTROL AND SAFETY</b>				
<b>EVACUATION</b>				
Autodialler system	•	•	•	•
Automatic rescue system	○	○	○	○
Behaviour of lifts in the event of fire (EN 81-73)	○	○	○	○
Connection to auxiliary power source (generator)	○	○	○	○
Pit water detector	○	○	○	○
Safety landing call cancelling	○	○	○	○
Firefighters lift (EN 81-72)		○		○
<b>ACCESS CONTROL</b>				
Zone cancelling, coded call	○	○	○	○
Compulsory stop at main floor	○	○	○	○
External call cancelling	○	○	○	○
Automatic car call cancelling	○	○	○	○
Independent entrance selection	○	○	○	○
Non-emergency outage	○	○	○	○
Emergency outage	○	○	○	○
<b>COMMUNICATIONS*</b>				
Pre-opening doors	○	○	○	○
Down collective control	○	○	○	○
Full collective control	○	○	○	○
Intercom system	○	○	○	○

\* In order to check out these options please consult with us.

• Standard ○ Optional